



Typ T PFA isoliertes doppeltes verdichtetes Thermoelement-Kabel / Draht (IEC) 1/0,2 mm Strang




50M



TYPE-T

10m



TYPE-T

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Typ T PFA isoliertes doppeltes verdilltes Thermoelement-Kabel/Draht (IEC)

PFA-Teflon-Zwillingsverdilltes Paar zum Verlängern oder Herstellen einfacher Thermoelemente. PFA-Teflon besitzt eine gute mechanische Festigkeit und Flexibilität und ist widerstandsfähig gegen Le, Suren und andere ungnstige Fissigkeiten, Gase, Dampf und Druck.

Technische Daten
Specifications

General Description	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility. PTFE better for steam/elevated pressure environments.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Single pair of PFA insulated conductors twisted together
Core / Strands	1/0.2
Conductor Cross Section 1/0.2 (mm²)	0.032
+ Colour	Brown
- Colour	White
Drain Wire	No
Insulation Material	PFA Teflon®
Loop Resistance 1/0.2 (Ohms per combined metre)	16.2
Max. Temperature	+260°C
Min. Temperature	-75°C
+ Conductor	Copper
- Conductor	Constantan



Screen	No
Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	T
Tolerance	Class 1