IEC-Mineralisoliert-Thermoelement mit Gewinde-Poti und 100 mm PFA-isoliertem Zwillingsverdrilltem IEC-Blei Typ K 1,0 mm x 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Mssen Sie Ihren Temperatursensor kalibrieren?

Labfacility ist auf ISO17025 (UKAS) Kalibrierungsstandards rckverfolgbar und bietet die Wahl zwischen einer 3- oder 5-Punkt-Rckverfolgbarkeit ber unsere hauseigene Kalibrierungseinrichtung.

Bitte beachten Sie, dass Sie, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufgen, bezglich Lieferinformationen kontaktiert werden.

Technische Daten

Specifications

Product Code	XE-3305-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.0mm
Probe Length	150mm
Sheath Material	310 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm
Termination Type	Bare Tails

Max. Temperature	750°C
Min. Temperature	-40°C
Standards Met	IEC 584
Series	Mineral Insulated