



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

IEC Mineralisiertes Thermoelement mit glatter Topfdichtung und 1 m PFA-isoliertem IEC-Kabel - Typ N - 1,0 mm x 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Mssen Sie Ihren Temperatursensor kalibrieren?

Labfacility ist auf ISO17025 (UKAS)-Kalibrierstandards rckfhrbar und bietet die Wahl zwischen einer 3- oder 5-Punkt-rckfhrbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung.

Bitte beachten Sie, dass Sie bezüglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufügen.

Leistungsbeschreibung**Specifications**

Product Code	XE-3161-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	N
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.0mm
Probe Length	150mm
Sheath Material	Nicrosil
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584)
Core / Strands	7/0.2mm
Termination Type	Bare Tails

Max. Temperature	1300°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	IEC 584