

**Mineralisiertes Thermoelement mit kompaktem
KNS-Anschlusskopf - Typ K - 6,0 mm
Durchmesser - 150 mm Länge**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Mssen Sie Ihren Temperatursensor kalibrieren?

Rckfhrbar auf ISO17025 (UKAS) Kalibrierstandards bietet Labfacility die Wahl zwischen einer 3- oder 5-Punkt-rckfhrbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung, Sie knnen beliebige Temperaturpunkte zwischen -10 C und +200 C auswhlen.

Bitte beachten Sie, dass Sie bezüglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufügen.

Leistungsbeschreibung**Specifications**

Product Code	XE-3321-001
General Description	Flexible mineral insulated probe with 310 stainless steel sheath
Sensor Type	Type 'K' (Nickel Chromium/Nickel Aluminium) to IEC 584
Thermocouple Junction	Insulated hot junction
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	6.0mm
Probe Length	150mm
Head Type	KNS, Cast aluminium finish, screw type lid with chain. Head fitted 2-way ceramic block
Gland	M16 x 1.5mm Plated brass gland fitted
Max. Temperature	+1100°C (Max temp of head is 170°C)
Min. Temperature	-40°C
IP Rating	IP67
Series	Mineral Insulated