Bi-Metall-Thermometer-TemperaturmessgerÃƒÂ¤te - RÃƒÂ¼ckeneinstiegsstil mit 1/2 "BSP-Tasche

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

**** Chemikalien -Kessel - Öfen - Gefrierschränke - Tankwagen - Lebensmittel- Getränke - Milch- Brauen - Temperaturgesteuerte Umgebungen ****

Für andere Stieldurchmessergrößen als 8 mm verwenden Sie bitte unser benutzerdefiniertes Bauformular mit der blauen Schaltfläche oben, um ein Angebot anzufordern.

Robuste Industrieklasse 1, Edelstahlgehäuse und Bajonettlünette mit 316 Edelstahlschaften. Hergestellt in 100mm Stirngrößen mit verschiedenen Längen und Durchmessern erhältlich. Temperaturbereiche von -20°C bis 200°C.

1 Jahr Garantie auf Arbeitsteile / Standard - Micro Adjustable Pointer

Optionales Kalibrierzertifikat

Sonderanfertigung auf Bestellung in ca. 4 Wochen. Sie werden nach der Bestellung mit einer Lieferzeit kontaktiert.

Leistungsbeschreibung

Specifications

Accuracy	Class 1 (1% F.S..D.)
Dial Size	100mm
Construction	Flush fitting bayonet locking case and bezel
Measuring Element	Bi-Metalic coil
Ranges °C	-20 to +40°C, 0 to +100°C, 0 to +120°C, 0 to +200°C
Over Limit Range	130% full scale
Stem / Bulb	316 Stainless steel
Case / Bezel ring	Stainless steel AISI 316L
Window	Glass
Dial	Aluminium, black figures on white
Pointer	Aluminium, black
Movement	Direct drive on back entry

Ambient Temperature	-10°C....+50°C
Temperature Effect	max...0,3% / 10°C
Protection EN 60 529	IP65