


**0,25 mm Durchmesser Schnell reagierendes
mineralisiertes Thermoelement mit glattem Topf
und PFA ANSI-Schwitzen - Typ K - geerdete
Verbindung - 100 mm Länge**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

[benutzerdefinierten Sensorformulare](#)

Bitte verwenden Sie unsere
, um Ihre Anforderungen für verschiedene MI-Längen und Kabeln zu be

Müssen Sie Ihren Temperatursensor kalibrieren?

Labfacility ist auf ISO17025 (UKAS)-Kalibrierstandards rückführbar und bietet die Wahl zwischen einer 3- oder 5-Punkt-rückführbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung.

Bitte beachten Sie, dass Sie bezüglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufügen.

Leistungsbeschreibung

Specifications

Product Code	XE-0803-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Sensor Type	Type K ANSI MA STYLE probes 0.25mm
Thermocouple Junction	Single element, grounded junction
Probe Length	100mm
Sheath Material	Stainless steel 316 sheath
Pot Type	Plain pot seal (200°C)
Cable Length	500mm
Cable Type	PFA insulated lead
Core / Strands	7/0.2mm
Cable Termination	Flat pair with tails
Max. Temperature	260°C
Min. Temperature	-40°C
Tolerance	A 1%+ Length Tolerance applies



Standards Met	ANSI
---------------	------