



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

0,5 mm schnell reagierende mineralisolierte Thermoelemente mit Miniatur-IEC-Stecker - isolierte Verbindungsstelle - 100 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Schnelles Ansprechen Mineralisoliertes Thermoelement in Typ K. Verschiedene Lngen erhltlich, mit IEC-Miniaturstecker (220 C) fr einen schnellen und einfachen Anschluss.

Fr Versionen mit einem Durchmesser von 0,25 mm, 0,75 mm und 0,81 mm verwenden Sie bitte unsere [benutzerdefinierten Sensorformulare](#), um Ihre Anforderungen zu bermitteln

Mssen Sie Ihren Temperatursensor kalibrieren?

Rckfhrbar auf ISO17025 (UKAS) Kalibrierstandards bietet Labfacility die Wahl zwischen einer 3- oder 5-Punkt-rckfhrbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung, Sie knnen beliebige Temperaturpunkte zwischen -10 C und +200 C auswhlen.

Bitte beachten Sie, dass Sie bezglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufgen.

Leistungsbeschreibung

Specifications

Product Code	XE-0161-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated or grounded from sheath
Probe Diameter	0.5mm
Probe Length	100mm
Sheath Material	Stainless steel 310
Termination Type	Miniature flat pin plug, colour coded in accordance IEC 584
Max. Temperature	+750°C. Plug Max. temperature range: 200°C
Min. Temperature	-40°C
Standards Met	IEC 584

Connector Type	Plug
Connector Size	Miniature