



LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Schnell ansprechendes Thermoelement mit 0,81 mm Durchmesser und Miniatur-IEC-Stecker - geerdete Verbindungsstelle - 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Wenn Sie grere Mengen bentigen, senden Sie bitte eine E-Mail sales@labfacility.com oder rufen Sie unsere Vertriebs hotline 01243 871280 an.

Mssen Sie Ihren Temperatursensor kalibrieren?

Labfacility ist auf ISO17025 (UKAS)-Kalibrierstandards rckfhrbar und bietet die Wahl zwischen einer 3- oder 5-Punkt-rckfhrbaren Kalibrierung mit unserer hauseigenen Kalibriereinrichtung.

Bitte beachten Sie, dass Sie bezüglich der Lieferinformationen kontaktiert werden, wenn Sie Ihrer Bestellung eine Kalibrierungsoption hinzufügen. .

Leistungsbeschreibung

Specifications

Product Code	XE-0229-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction grounded from sheath
Probe Diameter	0.81mm
Probe Length	250mm
Sheath Material	K - Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584) (Max Temp 250°C)
Core / Strands	7/0.2mm
Termination Type	Miniature flat pin plug, colour coded in accordance IEC 584



Max. Temperature	+650°C. Plug Max. temperature range: 200°C
Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	IEC 584
Connector Type	Plug
Connection Type	Miniature