

Hermetisch abgedichteter Draht-Thermistor-Sensor - 2m



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Hermetisch abgedichteter 2-Draht-10K-NTC-Thermistorsensor für korrosive oder nasse Umgebungen (Schutzart IP67)

Hauptmerkmale:

Widerstandswert: 10K Ohm

Typ: NTC-Thermistor (Negativer Temperaturkoeffizient), was bedeutet, dass sein Widerstand mit steigender Temperatur abnimmt.

Temperaturbereich: Kann Temperaturen von -30 C bis +150 C genau messen.

Verkabelung: 2-Draht-Konfiguration für einfache Konnektivität.

Ein IP67-Drahtsensor, der hermetisch abgedichtet ist und für den Einsatz in korrosiven oder nassen Umgebungen geeignet ist.

Dieser vielseitige Mehrzwecksensor wurde speziell für den Einsatz in und zum Schutz vor Korrosion in rauen oder nassen Umgebungen entwickelt. Er hat eine schnelle Reaktionszeit und lässt sich leicht reinigen. Der undurchlässige, PFA-isolierte flexible Drahtthermistor bietet eine außergewöhnliche Beständigkeit gegen Le, Flüssigkeiten, Gase und Chemikalien und ist elektrisch isoliert.

Die Spitze enthält einen 10K NTC-Thermistor, der schweißversiegelt ist, um eine durchgehende PFA-Beschichtung über die gesamte Länge zu erhalten und eine luftdichte und feuchtigkeitsbeständige Atmosphäre zu schaffen.

Typische Anwendungen

Pharmazie, Autoklaven und Sterilisation

Essen & Catering

Umwelt & Geothermie

Labor und Forschung & Entwicklung

Leistungsbeschreibung

Specifications

Product Code	XE-9875-001
General Description	An IP67 sensor that is hermetically sealed for use in corrosive or wet environments
Sensor Type	Hermetically sealed thermistor
Thermistor	10K NTC Thermistor
BETA 25/85	3977K



Cable Length	2m
Cable Type	2 wire flexible 7/0.2mm stranded conductors (24AWG) with 75mm tails
Core / Strands	7/0.2mm (24AWG)
Cable Termination	75mm Bare Tails
Max. Temperature	+150°C
Min. Temperature	-30°C
IP Rating	67
Accuracy	+/- 0.2K (over 0-70°C)
Important Information	Pressure tested at 40 PSI as standard
Series	Hermetically Sealed Thermistor Probes 10k