



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Typ K PFA isoliertes doppeltes verdichtetes Thermoelement-Kabel/Draht (JIS) 7/0,2 mm Strang



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Resistent gegen le, Suren, andere Nebenwirkungen und Fllsigkeiten. Gute mechanische Kraft und Flexibilit. PTFE ist besser fr Dampf- oder Hochdruckumgebungen.

Technische Daten

Specifications

General Description	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Single pair of PFA insulated conductors twisted together
Core / Strands	7/0.2mm
Conductor Cross Section 7/0.2 (mm²)	0.219
+ Colour	Red
- Colour	White
Drain Wire	No
Insulation Material	PFA Teflon®
Loop Resistance 7/0.2 (Ohms per combined metre)	4.5
Max. Temperature	260°C
Min. Temperature	-75°C
+ Conductor	Nickel Chromium
- Conductor	Nickel Aluminium
Screen	No
Standards Met	JIS (Japanese Industrial Standards)



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Thermocouple Type	K
-------------------	---